

FRESE CILINDRICHE PER CAVE (end mills)

8732

SCU



HSS-E-8%

Prod. SCU

Tipo a 2 taglienti elicoidali. Serie corta. DIN 327 B - UNI 8254 A - ISO 1641/1.
Dente frontale al centro. Attacco DIN 6535 HB/1835-1B. Tolleranza tagli. e8.
In acciaio SUPER-RAPIDO HSS-E al COBALTO 8%.

Ø	mm	2	2,5	3	3,5	4	4,5	5	5,5	6	6,5	7	7,5	8	8,5	9	9,5
Lungh. totale	mm	48	49	49	50	51	51	52	52	52	60	60	60	61	61	61	63
Lungh. tagliente	mm	4	5	5	6	7	7	8	8	8	10	10	10	11	11	11	13
Attacco Ø	mm	6	6	6	6	6	6	6	6	6	10	10	10	10	10	10	10
8732	Cad.	30,60	30,60	27,40	26,10	23,70	24,90	23,70	23,70	23,70	32,10	32,10	32,10	32,10	36,70	36,70	38,10
Ø	mm	10	11	12	13	14	15	16	17	18	19	20	22	25	30		
Lungh. totale	mm	63	70	73	73	73	79	79	79	79	88	88	88	102	102		
Lungh. tagliente	mm	13	13	16	16	16	19	19	19	19	22	22	22	26	26		
Attacco Ø	mm	10	12	12	12	12	16	16	16	16	20	20	20	25	25		
8732	Cad.	35,70	43,50	44,70	49,80	53,50	58,40	62,10	65,70	73,30	90,10	86,50	149,00	171,00	215,00		

8734

SCU



TiAIN



HSS-E-8%

Descrizione di riferimento vedi Art. 8732

In acciaio SUPER-RAPIDO HSS-E al COBALTO 8% con rivestimento TiAIN.

Ø	mm	4	5	6	8	10	12	14
Lungh. totale	mm	51	52	52	61	63	73	73
Lungh. tagliente	mm	7	8	8	11	13	16	16
Attacco Ø	mm	6	6	6	10	10	12	12
8734	Cad.	37,10	37,10	37,10	51,50	55,90	67,30	76,60
Ø	mm	16	18	20				
Lungh. totale	mm	79	79	88				
Lungh. tagliente	mm	19	19	22				
Attacco Ø	mm	16	16	20				
8734	Cad.	91,70	114,00	127,00				

8737

SCU



HSS-E-8%

Tipo a 2 taglienti elicoidali. Serie lunga. ISO 1641/1. Dente frontale al centro.

Attacco DIN 6535 HB/1835-1B. Tolleranza tagli. e8.

In acciaio SUPER-RAPIDO HSS-E al COBALTO 8%.

Ø	mm	3	4	5	6	8	10	12
Lungh. totale	mm	60	67	70	76	79	83	98
Lungh. tagliente	mm	9	13	16	16	19	22	28
Attacco Ø	mm	6	6	6	6	10	10	12
8737	Cad.	35,10	35,10	35,10	35,10	40,10	45,90	59,10
Ø	mm	14	16	18	20			
Lungh. totale	mm	102	108	114	132			
Lungh. tagliente	mm	32	32	35	38			
Attacco Ø	mm	12	16	16	20			
8737	Cad.	72,60	85,40	98,90	128,00			

8738

SCU



HSS-E-8%

Tipo a 2 taglienti elicoidali e punta semisferica. Serie corta. ISO 1641/1.

Attacco DIN 6535 HB/1835-1B. Tolleranza tagli. e8.

In acciaio SUPER-RAPIDO HSS-E al COBALTO 8%.

Ø	mm	3	4	5	6	7	8	9
Lungh. totale	mm	49	51	52	52	60	61	61
Lungh. tagliente	mm	5	7	8	8	10	11	11
Attacco Ø	mm	6	6	6	6	10	10	10
8738	Cad.	38,90	36,90	36,90	36,90	46,70	46,70	54,10
Ø	mm	10	11	12	13	14	15	16
Lungh. totale	mm	63	70	73	73	73	79	79
Lungh. tagliente	mm	13	13	16	16	16	19	19
Attacco Ø	mm	10	12	12	12	12	16	16
8738	Cad.	54,10	65,60	67,10	70,80	78,50	84,90	89,70
Ø	mm	18	20					
Lungh. totale	mm	79	88					
Lungh. tagliente	mm	19	22					
Attacco Ø	mm	16	20					
8738	Cad.	110,00	134,00					