

CHIAVI A BUSSOLA ATTACCO 1/2" DIN 3120-ISO 1174 (sockets)
969RA**GEDORE****Orig. Gedore - Art. 19**

In acciaio al CROMO-VANADIO. Esecuzione cromata.

Con alloggiamenti all'interno dell'attacco per le sfere di fermo dei cricchi e leve.

DIN 3124, ISO 2725-1.

Tipo con esagono interno.



1/2"

Apertura.....	mm	8	9	10	11	12	13	14
Lungh. totale.....	mm	38	38	38	38	38	38	38
969RA	Cad.	12,60	12,60	12,60	12,90	13,10	13,50	14,20
Apertura.....	mm	15	16	17	18	19	20	21
Lungh. totale.....	mm	39	39	39	39	40	40	41
969RA	Cad.	14,40	14,60	15,20	15,60	15,80	16,70	17,90
Apertura.....	mm	22	23	24	25	26	27	28
Lungh. totale.....	mm	41	41	41	41	41	41	43
969RA	Cad.	18,10	18,20	18,20	19,80	20,20	23,20	26,20
Apertura.....	mm	29	30	32	33	34	36	
Lungh. totale.....	mm	43	43	44	44	44	44	
969RA	Cad.	26,40	26,40	26,80	28,70	28,70	38,70	

969RB**GEDORE****Orig. Gedore - Art. D19**

Descrizione di riferimento vedi Art. 969RA

DIN 3124, ISO 2725-1 mis. in mm.

Tipo con poligono interno.



1/2"

Apertura.....	mm	8	9	10	11	12	13	14
Lungh. totale.....	mm	38	38	38	38	38	38	38
969RB	Cad.	12,60	12,60	12,60	12,90	13,10	13,50	14,20
Apertura.....	mm	15	16	17	18	19	20	21
Lungh. totale.....	mm	39	39	39	39	40	40	41
969RB	Cad.	14,40	14,60	15,20	15,60	15,80	16,70	17,90
Apertura.....	mm	22	23	24	25	26	27	28
Lungh. totale.....	mm	41	41	41	41	41	41	43
969RB	Cad.	18,10	18,20	18,20	19,80	20,20	23,20	26,20
Apertura.....	mm	29	30	32	33	34	36	
Lungh. totale.....	mm	43	43	44	44	44	44	
969RB	Cad.	26,40	26,40	26,80	28,70	28,70	38,70	
Apertura.....	poll	5/16	11/32	3/8	13/32	7/16	1/2	9/16
Lungh. totale.....	mm	38	38	38	38	38	38	38
969RB	Cad.	16,70	20,20	16,70	16,20	16,70	16,20	17,20
Apertura.....	poll	19/32	5/8	11/16	3/4	25/32	13/16	7/8
Lungh. totale.....	mm	39	39	39	40	40	41	41
969RB	Cad.	17,20	17,20	18,20	18,20	18,20	20,20	20,20
Apertura.....	poll	15/16	1	1.1/16	1.1/8	1.3/16	1.1/4	
Lungh. totale.....	mm	41	41	41	43	43	44	
969RB	Cad.	21,80	21,80	28,60	28,70	29,60	30,20	

969RBC
*new***GEDORE****Orig. Gedore - Art. C 19**

In acciaio al CROMO-VANADIO. Esecuzione cromata. Con impronta SPECIALE a C.

PER USO A MANO SU VITI E DADI CON IMPRONTA ESAGONALE METRICA E IN POLLICI
DIN 3124.

Possono essere impiegate anche su viti e dadi danneggiati o fuori tolleranza.



1/2"

Apertura.....	mm	10	12	13	15	16	17	18
Apertura.....	poll	3/8	-	1/2	19/32	5/8	-	11/16
Lungh. totale.....	mm	38	38	38	38	38	38	38
969RBC	Cad.	12,50	12,90	13,20	14,10	14,20	14,80	15,20
Apertura.....	mm	19	22	24	27	30	32	
Apertura.....	poll	3/4	-	15/16	1.1/16	1.3/16	1.1/4	
Lungh. totale.....	mm	38	38	38	41,5	41,5	41,5	
969RBC	Cad.	15,40	17,60	17,80	22,70	25,90	26,30	

969RBE**GEDORE****Orig. Gedore - Art. 19L**

Descrizione di riferimento vedi Art. 969RA

DIN 3124, ISO 2725-1.

Tipo lungo con esagono interno.



1/2"

Apertura.....	mm	10	11	12	13	14	15	16	17	18
Lungh. totale.....	mm	77	77	77	77	77	77	77	77	82
969RBE	Cad.	33,40	33,40	34,40	34,40	36,60	36,60	37,20	37,20	37,60
Apertura.....	mm	19	21	22	24	27	30	32	34	
Lungh. totale.....	mm	82	82	82	82	82	82	82	82	
969RBE	Cad.	37,60	45,30	47,10	49,20	49,30	53,20	57,00	59,10	

Aperture mm 16 - 18 - 21 con foro per leve.